



KT-EMRG-1400C

EMERGENCY BALLAST



PRODUCT FEATURES

INPUT VOLTS: 120/277V, 60Hz
LIGHT OUTPUT: 1400 Lumen
BATTERY: 6V Sealed NiCD
ILLUMINATION TIME: 90 Minutes
WARRANTY: 5 Years



OPERATING DETAILS

- For use in new or existing fixtures, with or without an AC ballast, where emergency lighting is needed.
- Operates one or two lamps in the emergency mode.
- Complies with CEC Efficiency Standards
- 2-in-1 LED indicator light and push-to-test switch (for mandated code compliance testing).
- Internal battery automatically connects to the fluorescent lamp(s) for minimum 90 minute emergency illumination via an internal solid-state transfer switch.
- A discharged battery completely recharges in 24 hours, via a fully automatic solid-state, two-rate charger.
- Features Time Delay Technology which helps to overcome end-of-life circuit protection.

LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates the following lamps under emergency power:

	T5 (W)		T5HO (W)	T8 (W)		T8HO (W)	T12 (W)		T12HO (W)
No. of Lamps	1	2	1 or 2	1	2	1	1	2	1
Wattage	14-35	14-28	24-54	17-59	17-40	44, 86	20-75	20-25, 34-40	95-215

	4-Pin CFL (W)		4-Pin Long CFL (W)		4-Pin GR10q (W)		T5 Circline (W)		T9 Circline (W)	U-Bend (W)	
	1	2	1	2	1	2	1	2	1 or 2	T8	T12
No. of Lamps	1	2	1	2	1	2	1	2	1 or 2	1 or 2	1 or 2
Wattage	13-57	13-42	18-55	18-50	10-55	10-38	22-55	22-40	20-40	32	34, 40

INITIAL LUMEN OUTPUT

LAMP TYPE	INITIAL LUMENS	
	1-Lamp	2-Lamp
T5 21W	1050	1100
T5 28W	1150	1225
T5HO 39W	1200	1300
T8 25W	1100	1200
T8 40W	1350	1400
T8HO 86W	1400	-
T12 40W	950	1050
T12HO 110W	1400	-

LAMP TYPE	INITIAL LUMENS	
	1-Lamp	2-Lamp
4-Pin CFL 42W	1160	1250
4-Pin Long CFL 36W	1050	1150
4-Pin GR10q 28W	900	975
T9 Circline 40W	900	1050
T5 Circline 40W	1100	1200
U-Bend T8 32W	825	900
U-Bend T12 40W	800	925

NOTE: In 2-lamp operation, lumens are equally split between the two lamps.




KT-EMRG-1400C

EMERGENCY BALLAST

PHYSICAL SPECIFICATIONS

CASE DIMENSIONS



LENGTH	13.40"
WIDTH	2.40"
HEIGHT	1.50"
CASE MATERIAL: Painted Steel (White Finish)	

MOUNTING

- UL listed for factory or field installation. Suitable for damp location.
- Can be mounted inside, on top, or remote from of the fixture.*
- Designed to be used in both switched and unswitched fixtures.

** When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.*

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-EMRG-1400C-DP	Distributor Pack	1	Quick Ship

CATALOG NUMBER BREAKDOWN

KT-EMRG-1400C-DP



Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.