



# KTLD-80-1-24V

## CONSTANT VOLTAGE LED DRIVER



### DESCRIPTION

LED Driver | 80W | 24V Constant Voltage Output | 120V Input

<b>DRIVER TYPE:</b> Constant Voltage LED Driver
<b>MAX. POWER:</b> 80W
<b>INPUT VOLTAGE:</b> 120Vac ±10%
<b>OUTPUT VOLTAGE:</b> 24Vdc
<b>DIMMING:</b> Fixed Output
<b>WARRANTY:</b> 5 Years



### PRODUCT FEATURES

- Meets FCC 47 CFR Part 15 (Class B) Consumer Limits
- Over Current and Short Circuit Protection
- Type 1 Outdoor, Suitable for Dry and Damp Locations
- UL 879, UL 8750 Recognized Component LED Power Unit and Signage Application
- Class 2 Output
- 90°C/194°F Maximum Case Temperature
- Input Frequency: 50/60 Hz
- THD: < 20%


## SPECIFICATIONS

### ELECTRICAL SPECIFICATIONS

Family	INPUT CHARACTERISTICS				OUTPUT CHARACTERISTICS				FEATURES
	Input Voltage	Input Power	Power Factor	Max. Current	Max. Output Power	Max. Current	Min. Current	Output Voltage	Efficiency
80W	120Vac	92W	>0.9	0.86A	80W	3.3A	0A	24Vdc	87%

### PHYSICAL SPECIFICATIONS

#### CASE DIMENSIONS



<b>LENGTH</b>	9.50"
<b>WIDTH</b>	1.70"
<b>HEIGHT</b>	1.18"
<b>MOUNTING</b>	8.90"
<b>CASE STYLE</b>	L5

#### STANDARD LEAD LENGTHS\*

<b>BLACK</b>	12.00"
<b>WHITE</b>	12.00"
<b>BLUE</b>	12.00"
<b>RED</b>	12.00"

Lead wires are 18 AWG  
105°C/ 600V, solid copper.


**CASE MATERIAL:** Metal

\*Consult Keystone for special lead length requirements.

### WIRING DIAGRAM



### HOT SPOT LOCATION



Actual tc point is noted on each LED driver label.



# KTLD-80-1-24V

## CONSTANT VOLTAGE LED DRIVER

### ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KTLD-80-1-24V-CP	Carton Pack	Pending	Active

### CATALOG NUMBER BREAKDOWN

# KTLD-80-1-24V-CP

