

KTLD-80-UV-24V

CONSTANT VOLTAGE LED DRIVER

DESCRIPTION

LED Driver | 80W | 24V Constant Voltage Output | 120-277V Input

DRIVER TYPE: Constant Voltage LED Driver
MAX. POWER: 80W
INPUT VOLTAGE: 120-277Vac ±10%
OUTPUT VOLTAGE: 24Vdc
DIMMING: Fixed Output
WARRANTY: 5 Years

PRODUCT FEATURES

- Meets FCC 47 CFR Part 15 (Class B) Consumer Limits at 120V Input and (Class A) Non-Consumer Limits at 277V Input
- Over Current and Short Circuit Protection
- Type 1 Outdoor, Suitable for Dry and Damp Locations
- UL Pending
- Class 2 Output
- 90°C/194°F Maximum Case Temperature
- Input Frequency: 50/60 Hz
- THD: < 20%


SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Family	INPUT CHARACTERISTICS				OUTPUT CHARACTERISTICS				FEATURES
	Input Voltage	Input Power	Power Factor	Max. Current	Max. Output Power	Max. Current	Min. Current	Output Voltage	Efficiency
80W	120-277Vac	93W	>0.9	0.86A @ 120V 0.40A @ 277V	80W	3.3A	0A	24Vdc	86%

PHYSICAL SPECIFICATIONS

CASE DIMENSIONS



LENGTH	9.50"
WIDTH	1.70"
HEIGHT	1.18"
MOUNTING	8.90"
CASE STYLE	L5

STANDARD LEAD LENGTHS*

BLACK	12.00"
WHITE	12.00"
BLUE	12.00"
RED	12.00"

Lead wires are 18 AWG
105°C/ 600V, solid copper.


CASE MATERIAL: Metal

*Consult Keystone for special lead length requirements.

WIRING DIAGRAM



HOT SPOT LOCATION



Actual tc point is noted on each LED driver label.



KTLD-80-UV-24V

CONSTANT VOLTAGE LED DRIVER

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KTLD-80-UV-24V-CP	Carton Pack	Pending	Active

CATALOG NUMBER BREAKDOWN

KTLD-80-UV-24V-CP

