

Check back often for updates. If the ballast you are looking for is not on this list, please contact us, and we will make every effort to evaluate compatibility. **Please note:** if the catalog number on your lamps do not end in /G2 please consult Keystone for correct compatibility list.

Note: Slight flickering or dim startup of the lamp is common, and lamp performance stabilizes within 2-3 seconds.
Note: Reduced Lamp Load is defined as (1) lamp performance on a 2 lamp ballast & (3 or 2) lamp performance on a 4 lamp ballast.

Yes
 N/A
 No

Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			120V	277V	120V	277V
Keystone	KTEB-254HO-UV-PS-SL	2	✓	✓	✓	✗
	KTEB-254HO-UV-PS/A	2	✓	✓	✓	✓
	KTEB-454HO-UV-PS	4	✓	✓	✓	✓
	KTEB-154HO-1-TP	1	✓	–	–	–
Advance	ICN-2S54	2	✓	✓	✓	✓
	ICN-2S54-N	2	✓	✓	✓	✓
	ICN-2S54-T	2	✓	✓	✓	✓
	ICN-2S54-90C-N	2	✓	✓	✓	✓
	IZT-2S54-D*	2	✓	✓	–	–
	IOP-2PSP54-SC	2	✗	✗	✗	✗
	ICN-4S54-90C-2LS-G	4	✓	✓	✓	✓
Espan	IOP-4PSP54-2LS-G	4	✗	✗	✗	✗
	VE454MVHRP	4	✓	✓	✓	✓
Fulham	RHA-UNV-254-LT5	2	✓	✓	✓	✓
	RHA-UNV-454-LT5	4	✗	✗	✓	✓
Fusion	FB254T5MVE	2	✓	✓	✓	✓
	FB454T5MVE	4	✓	✓	✓	✓
GE	GE254MVPS-F	2	✗	✗	✗	✗
	GE254MVPS90-A	2	✗	✗	✗	✗
	GE454MVPS90-F	4	✗	✗	✗	✗

*Reduced Dimming Range

1. Reduced lamp load is defined as (1) lamp performance on a 2 lamp ballast and (3 & 2) lamp performance on a 4 lamp ballast.
2. SmartDrive LED lamp compatibility is determined when ballast turns on LED lamp and the electrical characteristics of the LED lamp are stable and within designed operating specifications.
3. Keystone SmartDrive LED lamp compatibility does not make any guarantees of electrical performance or lifetime for ballasts listed on this chart that are not manufactured by Keystone.
4. **Ballast compatibility testing is performed with specific date codes. Please contact Keystone for more information on date code of ballasts tested.**
5. All data subject to change.

Specifications subject to change. Last revised on 9.6.16

Keystone Technologies | North Wales, PA | 800-464-2680 | KeystoneLEDsolutions.com

✓ Yes
 - N/A
 ✗ No

Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			120V	277V	120V	277V
Halco	EP254HO/PS/MV/MC	2	✓	✓	✓	✓
	EP454HO/PS/MV	4	✓	✓	✓	✓
Luma	BLF254-U	2	✓	✓	✓	✓
Maxlite	SKEU542HOP/SC	2	✓	✓	✓	✓
Osram	QHE2X54T5HO/UNV PSN	2	✓	✓	✓	✓
	QTP2X54T5HO/UNV PSN HT	2	✓	✓	✓	✓
	QHE 4X54T5HO/UNV PSN HT SCL{DOE}	4	✓	✓	✓	✓
	QTP4X54T5HO/ UNV PSN HT W	4	✓	✓	✓	✓
Pacific	EB-254PRS-U	2	✓	✓	✓	✓
Sunpark	U-2/54T5HO	2	✓	✓	✓	✓
Ultrasave	ER254120MHT-W	2	✓	✓	✓	✓
	ER454120MHT-W	4	✓	✓	✓	✓
Universal	B254PUNV-D	2	✓	✓	✓	✓
	B454PUNV-E	4	✓	✓	✓	✓
	B454PUNVHB-E	4	✓	✓	✓	✓

Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			347V	480V	347V	480V
Advance	HCN-2S54-90C-WL	2	✓	✓	✓	✓
	HCN-4S54-90C-2LS-G	4	✓	✓	✓	✓
Fulsion	FB454347T5E	4	✓	-	✓	-
Osram	QHE 4X54T5HO/347-480 PSN HT SCL	4	✓	✗	✓	✗

1. Reduced lamp load is defined as (1) lamp performance on a 2 lamp ballast and (3 & 2) lamp performance on a 4 lamp ballast.
2. SmartDrive LED lamp compatibility is determined when ballast turns on LED lamp and the electrical characteristics of the LED lamp are stable and within designed operating specifications.
3. Keystone SmartDrive LED lamp compatibility does not make any guarantees of electrical performance or lifetime for ballasts listed on this chart that are not manufactured by Keystone.
4. **Ballast compatibility testing is performed with specific date codes. Please contact Keystone for more information on date code of ballasts tested.**
5. All data subject to change.

Specifications subject to change. Last revised on 9.6.16

Keystone Technologies | North Wales, PA | 800-464-2680 | KeystoneLEDsolutions.com