S-LED-4-28-8XX-P

4′ LED STRIP FIXTURE



28W, 120-277V Input, 0-10V Dimming

PRODUCT FEATURES

- Powered by 0-10V dimming LED drivers
- Smooth diffused lens for an even appearance
- 0-10V dimming, 10% minimum
- Compatible with emergency LED drivers
- Compatible with 480-277V step down transformers
- Compatible with occupancy sensors
- Ambient operating temperature: -20ºC/-4ºF to 50ºC/122ºF
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- Power factor > 0.95
- L70 >50,000 hours

c UL us LISTED DLC LISTED **10 YEAR** LIMITED WARRANTY

AVAILABLE MODIFICATIONS (WITH VOLUME ORDER)

- Lumen targets
- Frame colors


PERFORMANCE SPECIFICATIONS

Catalog Number	Color Temp	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
S-LED-4-28-835-P	3500K	4′	120-277V	28W	>82	3584	128 lm/W
S-LED-4-28-840-P	4000K	4′	120-277V	28W	>82	3640	130 lm/W
S-LED-4-28-850-P	5000K	4′	120-277V	28W	>82	3696	132 lm/W

S-LED-4-28-8XX-P


4′ LED STRIP FIXTURE

PHOTOMETRIC SPECIFICATIONS



Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	782.1	21.8%
0-40	1,283.2	35.8%
0-60	2,307.4	64.4%
60-90	949.1	26.5%
70-100	668.2	18.7%
90-120	267.1	7.5%
0-90	3,256.5	90.9%
90-180	324.7	9.1%
0-180	3,581.2	100%

PHYSICAL SPECIFICATIONS



ORDERING INFORMATION

Catalog Number	Packaging Style	Quantity	Item Status
S-LED-4-28-835-P	Carton Pack	1	Active
S-LED-4-28-840-P	Carton Pack	1	Active
S-LED-4-28-850-P	Carton Pack	1	Active