

S-LED-8-54-8XX-P

8' LED STRIP FIXTURE



54W, 120-277V Input, 0-10V Dimming

PRODUCT FEATURES

- Powered by 0-10V dimming LED drivers
- Smooth diffused lens for an even appearance
- 0-10V dimming, 10% minimum
- Compatible with emergency LED drivers
- Compatible with 480-277V step down transformers
- Compatible with occupancy sensors
- Ambient operating temperature: -20°C/-4°F to 50°C/122°F
- UL Listed 1598: Suitable for dry and damp locations
- THD: <20%
- Power factor > 0.95
- L70 >50,000 hours



10 YEAR
LIMITED WARRANTY

AVAILABLE MODIFICATIONS (WITH VOLUME ORDER)

- Lumen targets
- Frame colors


PERFORMANCE SPECIFICATIONS

Catalog Number	Color Temp	Nominal Length	Input Voltage	Wattage	CRI	Lumen Output	Efficacy
S-LED-8-54-835-P	3500K	8'	120-277V	54W	>82	7100	131 lm/W
S-LED-8-54-840-P	4000K	8'	120-277V	54W	>82	7160	133 lm/W
S-LED-8-54-850-P	5000K	8'	120-277V	54W	>82	7210	134 lm/W


S-LED-8-54-8XX-P

8' LED STRIP FIXTURE

PHOTOMETRIC SPECIFICATIONS



PHYSICAL SPECIFICATIONS



ORDERING INFORMATION

Catalog Number	Packaging Style	Quantity	Item Status
S-LED-8-54-835-P	Carton Pack	1	Active
S-LED-8-54-840-P	Carton Pack	1	Active
S-LED-8-54-850-P	Carton Pack	1	Active