

KT-LED4.5FG16-E26-9XX-C
 REPLACEMENT LAMP

DESCRIPTION

4.5W G16 Lamp | 2700–5000K | ≥90 CRI | Small Globe



LAMP TYPE: Filament G16
BASE TYPE: E26 (Medium)
WATTAGE: 4.5W
COLOR TEMPERATURE: 2700–5000K
COLOR RENDERING INDEX (CRI): ≥90
WARRANTY: 3 Years
RATED LIFE: L70 (15,000 Hours)



TYPICAL APPLICATIONS

- Chandeliers
- Vanity Fixtures
- Decorative Accent Lighting
- Wall Sconces
- Pendant Lights

PRODUCT FEATURES

- Energy efficient, 80%+ energy savings over legacy equivalents
- Lower heat generation than legacy equivalents
- Smooth, uniform dimming
- Filament-style LED construction offers unique traditional appearance for decorative and mood-sensitive applications
- HiCRI LEDs offer enhanced color rendering vs. 80 CRI LEDs, providing ideal clarity, representation, uniformity of illuminated area/objects
- Long life minimizes replacement and maintenance costs
- Suitable for use in damp locations
- Operating temperature range –4°F/–20°C to 95°F/35°C
- PF >0.70
- Rated for open, recessed, and enclosed fixtures
- ANSI compliant construction ensures fitment for intended applications
- UL Listed
- Meets Energy Star requirements
- Complies with Part 15 of FCC
- Title 20 compliant

ELECTRICAL AND PERFORMANCE SPECIFICATIONS

Keystone Catalog Number	Description	Color Temp*	Input Voltage	Rated Lamp Wattage	Legacy Equivalent Wattage	Lumens	Efficacy	CRI	Base Type	Beam Angle	Dimmable
KT-LED4.5FG16-E26-927-C	G16 small globe filament bulb; Clear; Dimmable	2700K	120V	4.5W	40W incandescent	360 lm	80 lm/W	≥90	E26	360°	Yes
KT-LED4.5FG16-E26-930-C	G16 small globe filament bulb; Clear; Dimmable	3000K	120V	4.5W	40W incandescent	360 lm	80 lm/W	≥90	E26	360°	Yes
KT-LED4.5FG16-E26-950-C	G16 small globe filament bulb; Clear; Dimmable	5000K	120V	4.5W	40W incandescent	360 lm	80 lm/W	≥90	E26	360°	Yes

* Color Uniformity: CCT (Correlated Color Temperature) range as per guidelines outlined in ANSI C78.377-2017




ESSENTIAL SERIES

GENERAL PURPOSE LED BULBS

KT-LED4.5FG16-E26-9XX-C

REPLACEMENT LAMP

PHYSICAL CHARACTERISTICS



LAMP DIMENSIONS

A (Diameter)	1.97"
B (Length)	2.95"

BASE TYPE: E26 (Medium)

RATED LIFE

L70 (Hours)	15,000
-------------	--------

PACKAGING

Carton Quantity	24 pcs
Carton Dimensions	13.38" × 9.06" × 4.53"
Carton Weight	2.9 lbs

ORDERING INFORMATION

ORDER CODE	CARTON QUANTITY	ITEM STATUS	EASY CODE	UPC
KT-LED4.5FG16-E26-927-C	24 pcs	Active	OJB-14	843654129563
KT-LED4.5FG16-E26-930-C	24 pcs	Active	NSD-83	843654129570
KT-LED4.5FG16-E26-950-C	24 pcs	Active	RKU-91	843654129587

CATALOG NUMBER BREAKDOWN

KT-LED4.5FG16-E26-9XX-C

1 2 3 4 5 6 7 8 9

- 1 Keystone Technologies
- 2 LED Lamp
- 3 Wattage
- 4 Filament Bulb
- 5 Lamp Shape
- 6 Base Type
- 7 900 Series
- 8 Color Temperature
- 9 Clear Bulb