



KT-BPLED50-24-8XX-VDIM

BACKLIT LED PANEL LIGHT

DESCRIPTION

2'x4' LED panel light, 50W, 120-277V input, 0-10V dimming



PRODUCT FEATURES

- Aluminum frame featuring stepped edge design detail and gloss white paint for improved aesthetics
- New backlit style design; fits standard T-grid ceilings
- Suitable for recessed or surface mount (with optional accessories)*
- Construction features precise optical lenses over each individual LED, offering optimal light diffusion and consistent surface illumination, with no risk of yellowing over product lifetime
- Suitable for damp locations
- Powered by Keystone 0-10V dimmable LED driver with built-in junction box
- Compatible with Keystone SmartSafe LED emergency backup
- Over 50% energy savings compared to traditional fluorescent troffers
- Operating temp range -20°C/-4°F to 40°C/104°F


* For use in non-fire rated installations only

PERFORMANCE SPECIFICATIONS

Catalog Number	Input Voltage	Wattage	Color Temperature	Lumen Output	CRI	Power Factor	Efficacy	Lifetime
KT-BPLED50-24-835-VDIM	120-277V	50W	3500K	5,500	>80	>0.9	110 lm/W	50,000 Hours
KT-BPLED50-24-840-VDIM	120-277V	50W	4000K	5,500	>80	>0.9	110 lm/W	50,000 Hours
KT-BPLED50-24-850-VDIM	120-277V	50W	5000K	5,500	>80	>0.9	110 lm/W	50,000 Hours

PHOTOMETRIC SPECIFICATIONS


ISOCANDELA PLOT



Cd: 1,612, 90%	Cd: 716, 40%
Cd: 1,343, 75%	Cd: 537, 30%
Cd: 1,074, 60%	Cd: 358, 20%
Cd: 895, 50%	Cd: 179, 10%

----- Point of Max Cd: 1,103.3

POLAR CANDELA DISTRIBUTION




0° H
90° H
22.5° H
45° H
67.5° H

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30	1,399.3	26.4%
0-40	2,300.5	43.4%
0-60	4,101.5	77.3%
60-90	1,192.5	22.5%
70-100	528.0	10%
90-120	5.8	0.1%
0-90	5,293.9	99.8%
90-180	9.8	0.2%
0-180	5,303.7	100%

KT-BPLED50-24-8XX-VDIM
BACKLIT LED PANEL LIGHT

PHYSICAL SPECIFICATIONS




WEIGHT INFORMATION

1 Piece	1 Carton
11.5 lbs	23 lbs

EXPLODED VIEW

CONSTRUCTION FEATURES





KT-BPLED50-24-8XX-VDIM

BACKLIT LED PANEL LIGHT

WIRELESS CONTROL OPTIONS

Brand / System	Description	Ordering Number
Lutron Vive	FCJS-010 Wireless 0-10V fixture controller; 1A Max load; factory installed	KT-BPLED50-24-8XX-VDIM /FCJS0



ACCESSORIES (SOLD SEPARATELY)

Accessory	Catalog Number	Description
Emergency Battery Backup Mounting Kit	KT-BPLED-EM-22/4-KIT	Mounting Bracket for SmartSafe LED emergency backup for 2x2 and 2x4 backlit panels
Surface Mount Kit	KT-BPLED-SM-24-KIT	Surface Mount Kit 2x4 Backlit panels
J-Box	KT-BPLED-JBOX-1	Larger J-Box add-on for LED Backlit Panels, DLC Standard

ORDERING INFORMATION

CATALOG NUMBER	CARTON QTY.	EASY CODE	UPC
KT-BPLED50-24-835-VDIM-P	2	MLO-00	843654127804
KT-BPLED50-24-840-VDIM-P	2	XOA-13	843654127811
KT-BPLED50-24-850-VDIM-P	2	OZI-87	843654127828

CATALOG NUMBER BREAKDOWN

KT-BPLED50-24-8XX-VDIM

1 2 3 4 5 6 7 8

- 1** Keystone Technologies
- 2** Backlit Panel Light LED Fixture
- 3** Wattage
- 4** 2' x 4' Nominal Size
- 5** 800 Series
- 6** Color Temperature
- 7** 0-10V Dimming
- 8** Sensor Options

8 Sensor Options

	No option
/FC1-PIR	Occupancy sensor included