



ESSENTIAL SERIES

GENERAL PURPOSE LED BULBS

KT-LED12A19-0-9XX

REPLACEMENT LAMP

DESCRIPTION

12W Residential A19 Lamp | 2700–5000K |
>90 CRI | Omni-Directional



LAMP TYPE: Residential A19

BASE TYPE: E26 (Medium)

WATTAGE: 12W

COLOR TEMPERATURE: 2700–5000K

COLOR RENDERING INDEX (CRI): > 90

WARRANTY: 3 Years

RATED LIFE: 15,000 Hours



TYPICAL APPLICATIONS

- Table, desk, and floor lamps
- Wall sconces
- Surface-mount ceiling fixtures
- General lighting
- Pendant lights

PRODUCT FEATURES


- Energy efficient, 80%+ energy savings over legacy equivalents
- Lower heat generation than legacy equivalents
- Smooth, uniform dimming
- Durable plastic housing lowers the risk for breakage
- Smooth, diffused lens for comfortable glare-free performance
- HiCRI LEDs offer enhanced color rendering vs. 80 CRI LEDs, providing ideal clarity, representation, uniformity of illuminated area/objects
- Long life minimizes replacement and maintenance costs
- UL enclosed rated, suitable for use in totally enclosed luminaires
- Suitable for use in damp locations
- Operating temperature range –4°F/–20°C to 95°F/35°C
- PF > 0.90
- ANSI compliant construction ensures fitment for intended applications
- UL Listed
- Meets Energy Star requirements
- Complies with Part 15 of FCC
- Title 20 compliant
- Title 24 JA8 compliant (excluding 5000K lamps)

ELECTRICAL AND PERFORMANCE SPECIFICATIONS

Keystone Catalog Number	Description	Color Temp	Input Voltage	Rated Lamp Wattage	Legacy Equivalent Wattage	Base Type	Lumens	CRI	Beam Angle	Dimmable	Efficacy
KT-LED12A19-0-927	A19 bulb; Omni-directional; Dimmable	2700K	120V	12W	75W halogen	E26	1100 lm	>90	230°	Yes	92 lm/W
KT-LED12A19-0-930	A19 bulb; Omni-directional; Dimmable	3000K	120V	12W	75W halogen	E26	1100 lm	>90	230°	Yes	92 lm/W
KT-LED12A19-0-950	A19 bulb; Omni-directional; Dimmable	5000K	120V	12W	75W halogen	E26	1100 lm	>90	230°	Yes	92 lm/W

KT-LED12A19-0-9XX REPLACEMENT LAMP

PHYSICAL CHARACTERISTICS



LAMP DIMENSIONS

A (Diameter)	2.36"
B (Length)	4.43"

BASE TYPE: E26 (Medium)

PACKAGING

Carton Quantity	60 pcs
Carton Dimensions	15.55" × 13.07" × 10.55"
Carton Weight	11.75 lbs

ORDERING INFORMATION

ORDER CODE	CARTON QUANTITY	ITEM STATUS	EASY CODE	UPC
KT-LED12A19-0-927	60 pcs	Active	IAK-90	843654126548
KT-LED12A19-0-930	60 pcs	Active	SXV-04	843654126555
KT-LED12A19-0-950	60 pcs	Active	TDN-73	843654126562

CATALOG NUMBER BREAKDOWN

KT-LED12A19-0-9XX

1 2 3 4 5 6 7

- 1 Keystone Technologies
- 2 LED Lamp
- 3 Wattage
- 4 Lamp Shape
- 5 Omni-Directional
- 6 900 Series
- 7 Color Temperature